

STYCCOCLEAN C141

GENERAL PURPOSE CLEANER

PRODUCT DATA SHEET
PUBLISHED JANUARY 2000

SITE CONDITIONS VARY, TO ENSURE THIS PRODUCT IS SUITABLE AND TO CONFIRM THIS DATA SHEET IS CURRENT, PLEASE CALL OUR TECHNICAL SERVICES DEPARTMENT.

DESCRIPTION - A general purpose cleaner for removing contaminants such as grease, oil, etc. from the back of floorcoverings and accessories prior to installation. Also assists in the removal of some adhesives from the surface of carpets and floorcoverings.

USE ON - Most types of carpets and floorcoverings. Covings, nosings etc. made from linoleum, rubber, vinyl and metal. For cleaning metal tools after use, and cleaning formica or metal bench tops in workshops.

TOOLS - Clean absorbent white cloth. Small stiff bristle brush.

TECHNIQUES - Cleaning floorings and accessories.

Dampen a cloth with the cleaner and then rub the area to be cleaned until all the contamination has been removed. Take care not to use too much cleaner on rubber, linoleum, vinyl floorings or accessories as this may cause damage. When cleaning the back of floorings or accessories, allow all traces of the cleaner to evaporate before commencing installation, alternatively wipe dry to remove all the cleaner residues.

Removing adhesive from carpet.

Apply the cleaner gently with a cloth until the adhesive has been softened then remove the adhesive using a small stiff bristle brush. Take care not to rub softened adhesive residues further into the carpet pile.

PRECAUTIONS - The cleaner may damage floorings if left in contact too long. Test before use to ensure that the cleaner does not damage the material or affect the colour stability. May affect some plastics, check for suitability prior to use. Do not use on asphalt, tarmac or other materials which may be sensitive to this cleaner.

Do not allow the cleaner to penetrate the joints between floor tiles.

Do not apply onto a hot surface or any incandescent material. Observe the Health and Safety information provided.

HEALTH AND SAFETY ADVICE • Obtain the relevant **Material Safety Data Sheets** and follow the advice given.

DO NOT SMOKE - Do not expose to naked flames or permit contact with hot surfaces, this will create a fire risk.

DO NOT BREATHE THE VAPOUR - Inhalation can cause discomfort and distress.

Ensure adequate constant fresh air ventilation. Discharge vapour to a safe place in open air by natural or mechanical extraction.

AVOID PROLONGED CONTACT WITH SKIN - Use barrier cream or gloves for hands.

In case of contact with eyes, mouth or nose, wash with water and obtain medical attention.

IF SPILLED - Remove and dispose of in accordance with national and local regulations for waste materials.

Close container securely, immediately after use to prevent emission of vapour.

TECHNICAL CHARACTERISTICS

COLOUR	- Colourless.
CONSISTENCY	- Liquid.
SPECIFIC GRAVITY	- 1.02 Typical.
STORAGE	- Store between 5°C and 30°C.
SHELF LIFE	- 12 months in unopened containers stored under good conditions.
PACKAGES	- 1 litre and 250ml.



F. Ball and Co. Ltd.

Churnetside Business Park, Station Road, Cheddleton, Leek,
Staffordshire. ST13 7RS, United Kingdom.

Tel: +44 (0) 1538 361633 Fax: +44 (0) 1538 361622

(For technical service enquiries only Fax: +44 (0) 1538 361567)

E mail: webmaster@f-ball.co.uk Internet: www.f-ball.co.uk

